

Product Overview

Knowledge of the condition of transformers is essential for all electrical networks and on-line monitoring of critical transformers is increasingly vital. This information allows valuable assets to be maximised and expensive failures to be avoided.

Dissolved Gas Analysis (DGA) and moisture measurement of the insulation oil are recognised as the most important tests for condition assessment of transformers.

Features & Benefits

The TRANSFIX unit is a new generation of on-line DGA equipment giving essential insight into the condition of transformers.

Extensive field use proves that the TRANSFIX equipment provides reliable information and represents a valuable tool for Asset Management:

- Transformer faults detected in their infancy.
- Transformer output optimized safely, maximising asset
- Transformer ageing can be calculated.
- Type of fault can be classified from results.

DGA & Water

Eight gases plus moisture and nitrogen.

No Consumables

No carrier gases or calibration gases required.

Cutting edge technology

Kelman equipment brings DGA to a new level.

Minimal Maintenance

Reduces expense and inconvenience for user.

Comms Options

Extensive local and remote communications options.

Alarm Settings

Sophisticated programmable alarm system.



Reliable Gas Extraction

Internal modified head space gas extraction.

Sampling Rate

Sampling rates are configurable from daily to hourly. Caution and Alarm Modes can be used to increase the sampling rate. Alarm and caution thresholds are user-configurable. Circuits with higher alarm status will have priority in scheduling.

Kelman PERCEPTION*

Advanced asset management suite providing sophisticated graphical trending & diagnostic analysis of results.

Load Monitoring

Allows results to be analysed with the loading of the transformer.

Easy Installation

No outages required.

Local Display

LCD Display provides up to date information on site.

External Sensors

Additional inputs for up to five other sensors. Three 12 to 30VDC digital inputs.

Technical Specifications

PARAMETER (compound)	VALUE/MEETS (measurement range)
Hydrogen (H ₂)	5 - 5,000 ppm
Carbon Monoxide (CO)	2 - 50,000 ppm
Carbon Dioxide (CO ₂)	20 - 50,000 ppm
Methane (CH ₄)	2 - 50,000 ppm
Acetylene (C ₂ H ₂)	0.5 - 50,000 ppm
Ethane (C ₂ H ₆)	2 - 50,000 ppm
Ethylene (C ₂ H ₄)	2 - 50,000 ppm
Water (H ₂ O)	0-100% RS (given in ppm)
Oxygen (O ₂)	100 - 50,000 ppm
Nitrogen (N ₂)	10 - 130,000 ppm, accuracy ±15%
Accuracy	± 5% or ± LDL (whichever is greater)

ENVIRONMENTAL

Temperature Range	-40 to 55°C (-40 to 131°F)
Oil Temperature Range	-40 to 120°C (-40 to 248°F)
Power Supply	90 - 250 VAC; 47 - 63Hz; 150W; 8A max
Operating Humidity	10 - 95% RH non-condensing
Enclosure	IP55
Weight	78 kg (172 lbs)
Single Phase Alarm Relays	NO and NC provided, 5A 250 VAC, 5A 30 VDC.
Measurement Frequency	Variable - 1 per hour to 1 per day



Communications

- Two separate channels for remote communications, local USB connection and Ethernet connection.
- Communications protocols supported include MODBUS®, MODBUS/TCP, DNP3.0 and IEC®61850.
- Modules available for connection via RS232, RS485, Ethernet, PSTN modem and GSM or CDMA wireless modems.

Technical Features

- Uses photo-acoustic spectroscopy to give highly reliable results. Field proven in over ninety countries worldwide.
- Eight target gases plus moisture measured.
- Estimation of nitrogen and total gas content for free breathing transformers.
- Full embedded processor – over two years of data at a default sampling rate of one sample taken every four hours.
- Non-volatile memory storage to prevent loss of data.
- Discrete sampling gives more rapid response to gas rises. No ‘averaging’ of DGA results.

Alarms

- Two Sunlight Visible front panel LED Arrays (Red & Yellow) and six Alarm Relay contacts, each user configurable.
- All alarms can be set or changed locally or remotely using Kelman **PERCEPTION** PC Software.
- Six alarm setting screens or scenarios are available, which can set alarms based on the level of eight gasses, TDCG, and moisture, and rates of change for each gas.
- Each alarm setting screen can activate one of six alarm relays, the red or yellow front panel indicator or send a SMS message if equipped with the optional cellular GSM or CDMA modem.
- Six dry Alarm Relay contacts (configurable). NO and NC provided; 5A 250VAC, 5A 30VDC.
- Caution mode and alarm mode can be used to increase sampling frequency.
- The alarm results of each screen are independent of the other circuits and alarm setting screens.

GE Energy
Lissie Industrial Estate East
Lissie Road
Lisburn BT28 2RE
United Kingdom
+44 (0) 2892622915

www.kelman.co.uk
www.ge.com/energy

©2009 General Electric Company. All rights reserved.
* Trademarks of General Electric Company.
IEC is a registered trademark of Commission Electrotechnique Internationale.
Modbus is a registered trademark of Schneider Automation, Inc.
GEA17280 (02/09)

